

+

THREADED & FSW ENDS						FLANGED END								
VALVE SIZE	DIMENSIONS, INCHES					WGT. lbs.	VALVE SIZE	ANSI FLANGE	DIMENSIONS, INCHES					Wt. lbs.
	A	B	C	D	E				A1	B	C	D	E	
1/2	5.31	10.74	3.43	7.12	10.00	48	1/2"	150#	11.50	10.74	3.43	7.12	10.00	50
3/4	5.31	10.74	3.43	7.12	10.00	53		300#	11.50	10.74	3.43	7.12	10.00	52
1	5.68	11.06	3.56	7.12	10.00	58	3/4"	150#	11.50	10.74	3.43	7.12	10.00	57
1 1/4	6.00	11.43	3.75	7.12	10.00	58		300#	11.50	10.74	3.43	7.12	10.00	59
1 1/2	8.00	15.31	5.00	10.62	10.00	90	1"	150#	11.50	11.06	3.56	7.12	10.00	62
2	8.00	15.31	5.00	10.62	10.00	92		300#	11.50	11.06	3.56	7.12	10.00	64
							1 1/4"	150#	11.50	11.43	3.75	7.12	10.00	62
							300#	11.50	11.43	3.75	7.12	10.00	66	
							1 1/2"	150#	14.50	15.31	5.00	10.62	10.00	96
							300#	14.50	15.31	5.00	10.62	10.00	102	
							2"	150#	14.50	15.31	5.00	10.62	10.00	102
							300#	14.50	15.31	5.00	10.62	10.00	106	

  
  

SPECIFICATION DATA	
CUSTOMER _____	SERIAL No. _____
ORDER No. _____	TAG No. _____
VALVE TYPE _____	QTY. _____
BODY _____	
END CONN. _____	MAX. ΔP _____
INLET PRESS. _____	SET AT _____
TEMP. RANGE _____	VALVE ACTION: RISE IN TEMPERATURE TO <input type="checkbox"/> OPEN
	<input type="checkbox"/> CLOSE
	VALVE SEAT _____ Cv _____
	CAPILLARY LENGTH _____ BULB _____
MISC. _____	
CERTIFIED _____	DATE _____

  

**RICHARDS INDUSTRIES**  
CINCINNATI, OHIO  
U.S.A.

VALVE GROUP °

  

FN: MK87	DATE	5/31/96
	DRAWN BY	JLA
	CHECKED BY	
		MK87

  

1/2"-2" MARK 87  
EXTERNAL PILOT OPERATED TEMPERATURE REGULATOR

+