

+

THREADED & FSW ENDS					FLANGED END								
SIZE	MAT'L	DIMENSIONS, INCHES			WGT. LBS.	ANSI FLANGE SIZE	DIMENSIONS, INCHES				Wt. lbs.		
		A	B	C			D	A <sub>1</sub>	B	C		D	
1/2 & 3/4"	DI/BRZ	3.62	8.25	2.25	7.12	22	DI/BRZ	CS/SS	DI/BRZ	CS/SS	ALL	DI/BRZ	CS/SS
1"	CS/SS	3.62	8.25	2.25	7.12	23	7.25	8.25	8.25	8.25	2.25	7.12	24
1"	DI/BRZ	4.12	8.50	2.25	7.08	25	7.50	8.25	8.25	2.25	7.12	26	27
1"	CS/SS	4.18	9.00	2.65	7.12	25	7.25	8.25	8.25	2.25	7.12	26	27
1 1/4"	DI/BRZ	4.12	8.50	2.25	7.08	25	7.62	8.25	8.25	2.25	7.12	28	29
1 1/2"	DI/BRZ	4.50	8.75	2.37	7.08	28	7.25	8.50	9.00	2.65	7.12	29	29
1 1/2"	CS/SS	4.81	9.25	2.65	7.08	31	8.75	8.50	9.00	2.65	7.12	31	31
2"	DI/BRZ	4.50	9.00	2.50	7.08	26	7.87	8.50	8.50	2.25	7.08	29	29
2"	CS/SS	5.50	9.25	2.75	7.08	35	8.37	8.50	8.50	2.25	7.08	33	33
1 1/2"	150#	8.75	8.75	8.75	9.25	34	8.75	8.75	9.25	2.65	7.08	34	37
2"	150#	10.00	10.00	9.25	9.25	43	10.25	9.25	9.25	2.65	7.08	40	43
2"	300#	10.00	10.00	9.25	7.08	45	10.00	9.00	9.25	2.75	7.08	40	45
2"	300#	10.50	10.50	9.25	7.08	44	10.50	9.00	9.25	2.75	7.08	44	49

  

① NOT ANSI STD.  
② IFE ONLY

**MK55 & 65**

F.N.:MK55

CUSTOMER \_\_\_\_\_  
ORDER No. \_\_\_\_\_ SERIAL No. \_\_\_\_\_  
TAG No. \_\_\_\_\_  
VALVE TYPE \_\_\_\_\_ QTY. \_\_\_\_\_  
BODY \_\_\_\_\_  
END CONN. \_\_\_\_\_  
INLET PRESS. \_\_\_\_\_ MAX. Δ P \_\_\_\_\_  
PRESS. RANGE \_\_\_\_\_ SET AT \_\_\_\_\_  
VALVE ACTION: RISE IN PRESSURE TO  OPEN  CLOSE  
VALVE SEAT \_\_\_\_\_ Cv \_\_\_\_\_  
MISC. \_\_\_\_\_  
CERTIFIED \_\_\_\_\_ DATE \_\_\_\_\_

**RICHARDS INDUSTRIES**  
CINCINNATI, OHIO  
U.S.A.

VALVE GROUP \_\_\_\_\_

DRAWN BY \_\_\_\_\_ DATE \_\_\_\_\_  
JLA 4/9/96  
CHECKED BY \_\_\_\_\_ DATE \_\_\_\_\_

**MK55/65**

1/2-2" MARK 55 & 65  
VACUUM BREAKER AND VACUUM REGULATOR

+